

鋼管製ねじ込み管継手

INTRODUCE MANUFACTURERD GOODS to NAGOYA

検査圧力 (耐圧) 2.45Mpa { 25kgf/cm² } (水圧)

(漏れ) 0.49Mpa { 5kgf/cm² } (空圧)

品名		白・黒ニップル												黒片ネジニップル		
記号		WN・BN												BNS		
形状																
呼び径		D	L											L		
(A)	(B)		パレル	50	65	75	90	100	125	150	175	200	250	300	パレル	100
6	1/8	10.5	24	○	○	○	△	○	○	○	△	○	○	○	24	○
8	1/4	13.8	26	○	○	○	△	○	○	○	△	○	○	○	26	○
10	3/8	17.3	28	○	○	○	△	○	○	○	△	○	○	○	28	○
15	1/2	21.7	34	○	○	○	△	○	○	○	△	○	○	○	34	○
20	3/4	27.2	38	○	○	○	△	○	○	○	△	○	○	○	38	○
25	1	34.0	42	○	○	○	△	○	○	○	△	○	○	○	42	○
32	1 1/4	42.7	50		○	○	△	○	○	○	△	○	○	○	50	○
40	1 1/2	48.6	50		○	○	△	○	○	○	△	○	○	○	50	○
50	2	60.5	58		○	○	△	○	○	○	△	○	○	○	58	○
65	2 1/2	76.3	70					○	○	○		○	○	○	70	
80	3	89.1	78					○	○	○		○	○	○	78	
100	4	114.3	90					○	○	○		○	○	○	90	
125	5	139.8	103					○	○	○		○	○	○	103	
150	6	165.2	103					○	○	○		○	○	○	103	

※特殊サイズも承ります ・ △印 受注生産

品名		エポニップル (エポキシ樹脂コーティング製品)														
記号		E N														
形状																
呼び径		D	L											L		
(A)	(B)		パレル	50	65	75	90	100	125	150	175	200	250	300	パレル	100
6	1/8															
8	1/4															
10	3/8															
15	1/2	21.7	34	○	○	○	△	○	○	○	△	○	○	○		
20	3/4	27.2	38	○	○	○	△	○	○	○	△	○	○	○		
25	1	34.0	42	○	○	○	△	○	○	○	△	○	○	○		
32	1 1/4	42.7	50		○	○	△	○	○	○	△	○	○	○		
40	1 1/2	48.6	50		○	○	△	○	○	○	△	○	○	○		
50	2	60.5	58		○	○	△	○	○	○	△	○	○	○		
65	2 1/2	76.3	70					○	○	○		○	○	○		
80	3	89.1	78					○	○	○		○	○	○		
100	4	114.3	90					○	○	○		○	○	○		
125	5	139.8	103													
150	6	165.2	103													





※△印 受注生産



単位: mm



NAGOYA Co.,Inc



品名		VBニップル (水道用硬質塩化ビニルライニング鋼管)									
記号		VB									
形状											
呼び径		D	VB		L						
(A)	(B)		内面ライニング厚さ	近似内径	パレル	50	65	75	100	125	150
6	1/8										
8	1/4										
10	3/8										
15	1/2	21.7	1.5±0.2	13.1	34	○	○	○	○	○	○
20	3/4	27.2		18.6	38	○	○	○	○	○	○
25	1	34.0		24.6	42	○	○	○	○	○	○
32	1 1/4	42.7		32.7	50		○	○	○	○	○
40	1 1/2	48.6		38.6	50		○	○	○	○	○
50	2	60.5		49.9	58		○	○	○	○	○
65	2 1/2	76.3	64.9	70				○	○	○	
80	3	89.1	2.0±0.2	76.7	78				○	○	○
100	4	114.3		101.3	90				○	○	○
125	5										
150	6										

品名		HVAニップル (給湯用塩化ビニルライニング鋼管)									
記号		HVA									
形状											
呼び径		D	内面ライニング厚さ	近似内径	L						
(A)	(B)				50	60	75	100	125	150	
6	1/8										
8	1/4										
10	3/8										
15	1/2	21.7	2.5	11.1	○	○	○	○	○	○	○
20	3/4	27.2		16.6	○	○	○	○	○	○	○
25	1	34.0		22.6	○	○	○	○	○	○	○
32	1 1/4	42.7	3.0	29.7			○	○	○	○	○
40	1 1/2	48.6		35.6			○	○	○	○	○
50	2	60.5		46.9			○	○	○	○	○
65	2 1/2	76.3	3.5	60.9				○	○	○	○
80	3	89.1	4.0	72.7				○	○	○	○
100	4	114.3		97.3					○	○	○
125	5										
150	6										

単位: mm

鋼管製ねじ込み管継手

INTRODUCE MANUFACTURERD GOODS to NAGOYA

検査圧力 (耐圧) 2.45Mpa { 25kgf/cm² } (水圧)

(漏れ) 0.49Mpa { 5kgf/cm² } (空圧)

品名		白・ホースニップル		
記号		WHN		
形状				
呼び径		D	L	E × 数
(A)	(B)			
6	1/8	10.5	65	6.0×4
8	1/4	13.8	65	6.0×4
10	3/8	17.3	65	7.0×4
15	1/2	21.7	100	8.0×4
20	3/4	27.2	100	8.0×4
25	1	34.0	100	8.0×4
32	1 1/4	42.7	125	10.0×4
40	1 1/2	48.6	125	10.0×4
50	2	60.5	125	10.0×4
65	2 1/2	76.3	150	11.0×4
80	3	89.1	150	11.0×4
100	4	114.3	150	11.0×4
125	5			
150	6			

品名		白・黒本式サイホンニップル	
記号		WFM・BFM	
呼び径		10A(3/8B)	
形状			
品名		白・黒略式サイホン	
記号		WAM・BAM	
呼び径		10A(3/8B)	
形状			
品名		白・黒U式サイホン	
記号		WUM・BUN	
呼び径		10A(3/8B)	
形状			

品名		白・黒鉄ソケット (規格品)		黒鉄ハーフソケット	
記号		WS・BS		BHS	
形状					
呼び径		D	L	D	L
(A)	(B)				
6	1/8	15.0	19.0		
8	1/4	19.0	27.0	19.0	12.0
10	3/8	23.0	28.0	23.0	12.5
15	1/2	28.0	37.0	28.0	17.0
20	3/4	34.5	39.0	34.5	18.0
25	1	41.5	46.0	41.5	21.5
32	1 1/4	51.0	51.0	51.0	24.0
40	1 1/2	58.0	51.0	58.0	24.0
50	2	70.0	60.0	70.0	28.5
65	2 1/2	87.0	69.0		
80	3	102.0	75.0		
100	4	127.0	87.0		
125	5	154.0	96.0		
150	6	182.0	96.0		

※白製品は黒製品に電気メッキを施したもの

単位: mm



NAGOYA Co., Inc